

Declaration of Performance according to Regulation (EU) 305/2011

Product		Iron Dog 01
Intended use		Space heating in buildings
Manufacturer		Ulrich Brunner GmbH
Adress of the manufacturer		Zellhuber Ring 17-18 84307 Eggenfelden
System for assessment and verification of constancy of performance of the construction product.		System 3
The notified testing laboratory has carried out initial testing according to system 3		
Notified laboratory		139
Test report		RRF-AoP 24 1643
Harmonized technical specification		EN 16510-2-1:2022
Essential characteristic		
Safety in case of fire		
Protection of combustible materials	Minimum distances to combustible materials	
	bottom	d _B = 150 mm
	floor in front	d _F = 1500 mm
	ceiling	d _C = 750 mm
	rear	d _R = 800 mm
	side	d _S = 800 mm
	side radiation area	d _L = 1500 mm
	adjacent combustible materials (e.g. furniture)	d _P = 2000 mm
	material type and thickness of protective insualtion material	NPD
Hygiene, health and the environment		
At nominal heat output at 13% O ₂	Carbon monoxide emission (CO)	= 1250 mg/m3
	Nitrogen oxides emissions (NO _x)	= 200 mg/m3
	Emission of organic gaseous carbon (OGC)	= 120 mg/m3
	Particulate matter emissions (PM)	= 40 mg/m3
At part load heat output at 13% O ₂	Carbon monoxide emission (CO)	NPD
	Nitrogen oxides emissions (NO _x)	NPD
	Emission of organic gaseous carbon (OGC)	NPD
	Particulate matter emissions (PM)	NPD
Safety and accessibility in use		

Data for installation to a chimney at nominal heat output	Flue gas outlet temperature	349 °C
	Minimum flue draught	12 Pa
	Flue gas mass flow	6,3 g/s
Data for installation to a chimney at part load heat output	Flue gas outlet temperature	NPD
	Minimum flue draught	NPD
	Flue gas mass flow	NPD
Data for installation to a chimney regarding fire safety	Fire safety of installation to the chimney	NPD
Energy economy and heat retention		
Appliance's thermal output and energy efficiency at nominal heat output	Space heat output	7,0 kW
	Water heat output	NPD
	Efficiency	80,6 %
Appliance's thermal output and energy efficiency at part load heat output	Space heat output	NPD
	Water heat output	NPD
	Efficiency	NPD
Space heating efficiency	Seasonal space heating efficiency	65,0 %
	Energy efficiency index (EEI)	107
	Energy efficiency classification	A+
	Electric power consumption at nominal heat output	NPD
	Electric power consumption at part load heat output	NPD
	Standby mode power consumption	NPD
Sustainable use of natural resources		
	Environmental sustainability	NPD

The performance of the product corresponds to the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer in accordance with Regulation (EU) No. 305/2011.

Signed for and on behalf of the manufacturer:

A handwritten signature in black ink, appearing to read 'H. Brunner', written over a horizontal line.

Eggenfelden, 13.07.2026

Hubertus Brunner, CEO